



**Manchester
Metropolitan
University**

Lee, WD ORCID logoORCID: <https://orcid.org/0000-0003-4494-468X>, Ec-tors, Wim, Bae, Yun Kyung and Kim, Jinhee (2019) Heterogeneous Effects of Pedestrian Environments on Walkability by Spatial Cognition Level and Travel Contexts: A Latent Class Ordered Choice Approach. Transportation Research Record. ISSN 0361-1981 (In Press)

Downloaded from: <https://e-space.mmu.ac.uk/619938/>

Publisher: SAGE Publications

Please cite the published version

<https://e-space.mmu.ac.uk>

Transportation Research Record

Heterogeneous Effects of Pedestrian Environments on Walkability by Spatial Cognition Level and Travel Contexts: A Latent Class Ordered Choice Approach --Manuscript Draft--

Full Title:	Heterogeneous Effects of Pedestrian Environments on Walkability by Spatial Cognition Level and Travel Contexts: A Latent Class Ordered Choice Approach
Abstract:	<p>Measuring the pedestrian walkability is extensively emerged in urban planning and transportation area in the last decade, pointing to the walkable city. Previous studies have supposed to calculate the 'Walkability index', in terms of universal walking accessibility based on the walking facilities and street design indices. This approach implied the homogeneous perception of pedestrians, in order to assess the universal walking accessibility upon the road facilities. However, recent studies giving rise to claim that conventional approach is disesteem to the substances of personal contexts, which gained from the preceding experiences or memories of prior walking trips. The present study is position to the progress for heterogeneous perception of pedestrian satisfactions in relation to the contextual factors, such as sociodemographic attributes, spatial cognition level as the location familiarly, and the trip information. This study employing an advanced discrete choice modelling approach to develop the pedestrian walkability Latent Class Ordered Probit Choice model, it facilitates the influence of all the factors and their effects on the heterogeneity in walkability. The analysis results initialise the distinctive responses of walkability in relation to pedestrian latent groups, which can lead the attention to the variability of individual contextual variables. To this end, the paper presents more profound insights of pedestrian walkability, not only indicate the response of pedestrian environments, but also reveal the distinctive preferences on walkability between individuals.</p>
Manuscript Classifications:	Pedestrians and Bicycles; Bicycle and Pedestrian Data ABJ35SB; Bicycle/Pedestrian Performance Measures; Pedestrians ANF10; Safety and Human Factors; Behavior, Society, and Analysis; Pedestrians ANF10
Manuscript Number:	20-00398
Article Type:	Presentation and Publication
Order of Authors:	Won Do Lee
	Wim Ectors
	Yun Kyung Bae
	Jinhee Kim

1 **Heterogeneous Effects of Pedestrian Environments on Walkability by Spatial Cognition**
2 **Level and Travel Contexts: A Latent Class Ordered Choice Approach**

3
4 **Won Do Lee**

5 Crime and Well-being Big Data Centre
6 Manchester Metropolitan University, Manchester, England, M15 6BH
7 Email: W.Lee@mmu.ac.uk

8
9 **Wim Ectors**

10 Transportation Research Institute (IMOB)
11 Hasselt University, Diepenbeek, Belgium, 3590
12 Email: wim.ectors@uhasselt.be

13
14 **Yun Kyung Bae**

15 Infrastructure Policy Research Center
16 National Infrastructure Research Division
17 Korea Research Institute for Human Settlements, Sejong, Republic of Korea, 30147
18 Email: ykbae@krihs.re.kr

19
20 **Jinhee Kim, Corresponding Author**

21 Department of Urban Planning and Engineering
22 Yonsei University, Seoul, Republic of Korea, 03722
23 Email: kim.jinhee@yonsei.ac.kr

24
25 Word Count: 5,216 words + 3 tables = 5,966 words

26
27
28 *Submitted [July 30th, 2019]*
29

1 **ABSTRACT**

2 Measuring the pedestrian walkability is extensively emerged in urban planning and transportation
3 area in the last decade, pointing to the walkable city. Previous studies have supposed to calculate
4 the ‘Walkability index’, in terms of universal walking accessibility based on the walking facilities
5 and street design indices. This approach implied the homogeneous perception of pedestrians, in
6 order to assess the universal walking accessibility upon the road facilities. However, recent studies
7 giving rise to claim that conventional approach is disesteem to the substances of personal contexts,
8 which gained from the preceding experiences or memories of prior walking trips. The present
9 study is position to the progress for heterogeneous perception of pedestrian satisfactions in relation
10 to the contextual factors, such as sociodemographic attributes, spatial cognition level as the
11 location familiarly, and the trip information. This study employing an advanced discrete choice
12 modelling approach to develop the pedestrian walkability Latent Class Ordered Probit Choice
13 model, it facilitates the influence of all the factors and their effects on the heterogeneity in
14 walkability. The analysis results initialise the distinctive responses of walkability in relation to
15 pedestrian latent groups, which can lead the attention to the variability of individual contextual
16 variables. To this end, the paper presents more profound insights of pedestrian walkability, not
17 only indicate the response of pedestrian environments, but also reveal the distinctive preferences
18 on walkability between individuals.

19
20 **Keywords:** Walkability, Pedestrian Contexts, Pedestrian Contextual Groups, Latent Class
21 Ordered Probit Model, Spatial Cognition Level

1 INTRODUCTION

2 In recent years, it has increasingly been recognised the ‘walkability’ research, in terms of
3 measuring the level of pedestrian satisfaction. It becoming a very popular topic for both urban
4 planners and researchers have interested in the sustainable city (1). Previous studies have
5 revealed the significant indicators based upon the (pedestrian) environments factors to measure
6 the walking accessibility (2). Furthermore, empirical studies in US (1, 3–9) mainly complement
7 to calculate the walkability based on the street design (8, 10) and environmental facilities.
8 Overall, these studies paid attention to develop the universal measure of walking accessibility,
9 and also investigate the (dominant) effects of environmental (pedestrian) facilities.

10
11 However, previous studies have intend the inherent perceptions, i.e., fixed effects, of
12 pedestrians; (surrounded) environment facilities to account for their walking satisfaction (11,
13 12). In critique of these conventional studies, this study aiming to audit the heterogenous
14 perception of walkability response to pedestrian environment, in terms of the distinctive
15 perceptions of walking facilities of individuals. In this context, walkability may vary with
16 personal characteristics, such as socio-demographics and spatial cognition levels, and also take
17 into account for the retained perceptions (i.e. random effects), such as prior walking journeys. In
18 addition to their retained perceptions, pedestrians recognised their surroundings while walking,
19 so personal walking experiences, from their routine and habitual daily travels, providing the
20 distinctive perception of walking environments. It supports to investigate a comprehensive set of
21 psychological and environmental factors (2, 13).

22
23 To support this extensive perspective, the latest studies (2, 12, 14–17) claiming the
24 shortcoming of conventional researches, in which were supposed to be “one size fits all” (6).
25 These studies also demonstrate the impact of environmental factors on the walkability might be
26 overwhelmed, yet the substances of individual characteristics and contextual factors are
27 disesteemed. For instance, Lee et al. (2) estimated the walkability indicators using discrete
28 choice modelling approach, to exhibit the personal experience and contexts are dominant factor
29 to influence on walkability than walking facilities and land-use indices. Building on this
30 foundation, Erath et al. (17) developed a software tool that integrates the results from behaviour
31 surveys with network-based walking facility datasets, to compute the walkability index
32 incorporate with user preferences. Additionally, these studies also addressed the heterogeneous
33 effects on walkability, which generated by the difference in individual trip characteristics:
34 utilitarian and recreation trips (2, 13, 19) and fixed and flexible trip purpose (12), respectively.

35
36 In overview, this study supports the alternative approach, not only demonstrate the level
37 of pedestrian satisfaction, but also examine the heterogenous perception to walking facilities by
38 pedestrian contextual variables. To achieve this task that the research examines the distinctive
39 influence of pedestrian environments on walkability coupling with the pedestrian contexts, in
40 regard to their previous travel experiences; for instance, sociodemographic attributes, spatial
41 cognition level as the location familiarly, and the trip characteristics. Additionally, external
42 conditional attributes such as weather conditions and crowdedness, in terms of relative excessive
43 population volumes in relative to average pedestrian volumes at each survey location by the
44 course of the day, are also considered as kind of contextual factors. To simultaneously consider
45 all the factors and their effects on the heterogeneity in individual walkability, an advanced
46 discrete choice modelling approach (i.e., Latent Class Ordered Probit Choice model) is

1 employed. This approach is allowing to provide more profound insights into the relationship
2 between pedestrian environments, not only identifying the heterogeneous responses on
3 pedestrian walkability, which simultaneously estimating why people feel differently (i.e. the
4 contextual effects), but also interrogating what extent they feel differently with respect to the
5 pedestrian walkability. Therefore, empirical results using this approach could be deliver the
6 viable insight to urban planners, who aim to establish walkable cities with enhanced urban streets
7 for everyone with resulting from a better understanding of walkable pedestrian environment
8 design criteria. In the present study, the model was estimated based on 83,291 responses of
9 ‘Seoul Pedestrian Survey’ administered in November 2009 in Seoul, Korea.

10
11 This paper is structured in the following manner. In the next section, the data deployed in
12 this research is described, it provides the details of data resources; the survey information and
13 explanatory variables. In section three, the analytical strategy of the research is present the
14 deployed approach, i.e., the Latent Class-Ordered Probit Model. The model estimation results are
15 presented and described at the section four. Finally, we discuss the empirical summarises of the
16 research findings.

17 18 **DATA USED**

19 The ‘Seoul Pedestrian Survey’ was conducted in the whole Seoul area from September to
20 November in 2009. There were two stages in the survey data collection; on one hand an interview
21 was taken from respondents, on the other hand various pedestrian environemtal charteristics were
22 investigated and recorded, such as pedestrian flow (in volumes per hour), walking road width,
23 obstacles, pedestrian-support facilities (e.g., fence), and so forth. At each survey location,
24 surveyors collected responses from 24 pedestrians on Tuesdays, Wednesdays, and Fridays,
25 yielding 72 responses per location. Up to 2,400 individuals per day were interviewed (Seoul Metro
26 Government, 2010). The questionnaire collected the pedestrian walkability, the pedestrian’s
27 activity–travel, and personal information. There were over 1,170 survey locations, totalling 83,291
28 responses (Lee et al., 2018, page 1).

29
30 Based on the extensive dataset, we selected important variables and manipulated some of
31 them to represent pedestrian environment and pedestrian contexts. **Table 1** presents the variables
32 used for this study. First, the pedestrian walkability is considered which was measured by 3 ordinal
33 scales: uncomfortable, neutral, and comfortable. The survey asked the respondents to indicate how
34 much they feel comfortable to walk through the survey area. In addition, the respondents were
35 asked to provide some information regarding pedestrian contexts such as socio-demographics,
36 familiarity of the area, and trip characteristics. There are two variables to represent the familiarity
37 of the area: residential location (whether or not the location is in the same administriative district
38 with the survey location), and vsiting frequency of the area. The familiarity of the area is employed
39 to measure the spatial cognitive level of each respondent. We assume that people who live close
40 to the survey location and/or visit the location very frequently tend to be familiar with the area,
41 and thus that they have a higher level of spatial cognition with respect to the area. Two variables
42 were selected to represent the trip characterics of each respondent: trip purpose and travel
43 companion (whether to walk with others or not).

44
45
46

1 **TABLE 1 Variable Lists with Descriptive Information of the Sample**

Variable			Data Type	Attributes	Sample Distribution
Pedestrian walkability			Ordinal	Uncomfortable Neutral Comforable	40.1% 41.9% 18.0%
Pedestrian contexts	Socio-demographics	Gender	Nominal	Male Female	44.6% 55.4%
		Age	Ordinal	Teenager (Ages 15-19) Adults (Ages 20-59) Elderly (Ages over 60)	7.0% 79.3% 13.7%
	Familiarity	Residence in the same administrative district with the survey location	Nominal	Yes (Dweller) No (Stranger)	54.3% 45.7%
		Visiting frequency	Ordinal	Every day 3–5 days/week 1-2 days/week Rarely (1-3 days for 6 months and first visit)	40.4% 31.2% 14.2% 14.2%
		Trip characteristics	Trip purpose	Nominal	Utilitarian Others
	Travel companion		Nominal	With others Alone	73.0% 27.0%
	Pedestrian environments	Facility characteristics	Walking road width	Ratio	Meter
Presence of central lines			Nominal	Yes No	61.5% 38.5%
Number of total road lanes			Ratio	Lanes	mean: 3.47 std.: 2.64
Presence of walking obstacles			Nominal	Yes No	94.2% 5.8%
Mixed traffic street			Nominal	Yes No (Pedestrian only or with bike)	29.8% 70.2%
Presence of sidewalk fence			Nominal	Yes No	19.2% 80.8%
Presence of crossings			Nominal	Yes No	57.1% 42.9%
Presence of public transit stations within 50m			Nominal	Bus and subway Bus or subway Nothing	7.8% 31.6% 60.6%
Survey points characteristics		Crowdedness (Time-based)	Continuous	1 = average	mean: 0.993 std.: 0.374
		Type of spot	Nominal	Main road Residential area Others	14.1% 17.9% 68.0%
		Land-use mix	Continuous	Continuous	mean: 0.93 std.: 0.03


1 Variables representing the conditions of pedestrian environments can be classified into the
2 facility characteristics and the survey point's characteristics. The pedestrian facilities have
3 gathered during the survey periods to report the capability of pedestrian facilities, which
4 encompassing the surrounding area (within 50m ranges) of each survey points. In other words, the
5 pedestrian facilities depict the multitude typology of survey spots incorporate with the adjacent
6 arterial road attributes. There are three kinds of environmental facilities, which describing the
7 amenity level of pedestrian facilities as follows: 1) The constitutional survey spot facilities, such
8 as the walking road width, and mixed traffic street. 2) The characteristics of adjacency roads, it
9 comprising the number of total road lanes, and the installation of safeguard amenities for
10 pedestrians: sidewalk fence, crossings, and walking obstacles. Additionally, in terms of walking
11 obstacle that retraining the inconvenience of walking experiences to pedestrians, such as street
12 trees, distribution transformer, street lights, and so forth. Finally, 3) convenience to the public
13 transits (i.e. accessibility within 50m).

14
15 Subsequently, the land use information of each survey points are also take into account for
16 illustrating the typology of survey spots and adjacent arterial road areas. Crowdedness was
17 measured by the periodic levels of pedestrian volumes in contrast to the average daily pedestrian
18 volumes at each survey spots. As described in Lee et al (2), the pedestrian volumes may lead to
19 establish the impression of the area, and further pedestrians may be obtained the walkability scores
20 whereas retained by their walking experience. To account for this, the time-sensitive crowdedness
21 index was employed to take account for the variation of pedestrian volumes by four periods per
22 day at each survey points, if the value is equal to 1, it represents the sporadic pedestrian volume is
23 equal to the average volume. A value lower or higher than one indicates, reprehensively, a lower
24 or higher than usual volume.

25 26 27 **METHODOLOGY**

28 This study employs a latent class choice approach. The underlying theory of the latent class
29 choice approach assumes that a number of classes exists within the population, and that preferences
30 of the individuals involved in a class tend to be homogeneous, but each of classes has different
31 preferences. However, which class contains any particular individual is unknown to the analyst.
32 The approach estimates simultaneously the probability that an individual is included in each latent
33 class and the probability that the individual chooses a certain alternative across different classes
34 (24). This approach is generally accepted in many transportation studies in order to investigate
35 heterogeneity in travel behaviour. Application domains include, for instance, household location
36 decisions (25), route choice behaviour of truck drivers (26), bicycle parking preferences of train
37 travellers (27), preference of alternative-fuel vehicles (28), and departure time choice of train
38 commuters (29).

39



1
2 **Figure 1. Latent Class Order Probit Model framework.**
3

4 In this study, a latent class ordered probit model is developed to account for the ordinal
5 nature of the dependent variable (i.e. pedestrian walkability) and the heterogeneous effects of
6 attributes (i.e. pedestrian environments) on the dependent variable. **Figure 1** depicts the model
7 framework of this study. We assume that the level of pedestrian walkability indicated by an
8 individual is associated with the utility of the individual stemming from the pedestrian
9 environments (i.e. facility characteristics, crowdedness, and land-use characteristics) and that the
10 utility varies according to the pedestrian contexts with respect to the individual (i.e. socio-
11 demographics, familiarity, and trip characteristics). Based on this, the probability that individual
12 n indicates j th ordinal value for the walkability of pedestrian passage l can be formulated as
13 follows:
14

15
$$P_{nl}(j) = \sum_{q \in Q} H_n(q) P_{nl}(j|q) \quad (1)$$

16 where $H_n(q)$ is the probability that individual n involves in pedestrian-context class q , which is
17 called as the class membership probability. The latent class modelling approaches generally
18 suggest estimating the probability based on the formulation of the multinomial logit model as
19 follows:
20

21
$$H_n(q) = \frac{\exp(\theta_q \mathbf{Z}_n)}{\sum_{g \in Q} \exp(\theta_g \mathbf{Z}_n)} \quad (2)$$

22
23

1 where \mathbf{Z}_n indicates a $(M \times 1)$ vector of the pedestrian context variables with respect to individual
 2 n , and $\boldsymbol{\theta}_q$ is a $(1 \times M)$ vector of parameters corresponding to pedestrian-context class q .

3 In equation (1), $P_{nl}(j|q)$ is the conditional probability that individual n indicates j th
 4 ordinal value for the walkability of pedestrian passage l in the context of class q . We employed a
 5 system of ordered probit model for representing individual's decision-making process regarding
 6 ordinal scale of the walkability as follows:

$$7 \quad U_{lnq} = \boldsymbol{\beta}_q \mathbf{X}_{ln} + \varepsilon_{lnq}, \quad (3)$$

$$8 \quad y_{ln} = \begin{cases} 1, & \mu_{q,0} < U_{lnq} < \mu_{q,1} \\ 2, & \mu_{q,1} < U_{lnq} < \mu_{q,2} \\ \dots & \dots \\ 10 \quad j, & \mu_{q,j-1} < U_{lnq} < \mu_{q,j} \\ \dots & \dots \\ J, & \mu_{q,J-1} < U_{lnq} < \mu_{q,J} \end{cases} \quad (4)$$

11 where U_{lnq} is the utility of individual n with respect to pedestrian passage l in the context of class
 12 q , which consists of the systematic utility $\boldsymbol{\beta}_q \mathbf{X}_{ln}$ and the random disturbance ε_{lnq} . \mathbf{X}_{ln} indicates a
 13 $(K \times 1)$ vector of the pedestrian environment variables with respect to pedestrian passage l , and
 14 $\boldsymbol{\beta}_q$ is a $(1 \times K)$ vector of parameters representing the effects of the pedestrian environment
 15 variables on the utility which varies according to pedestrian-context class q . y_{ln} means an ordinal
 16 value for the walkability indicated by individual n with respect to pedestrian passage l . According
 17 to equation (4), the model assumes that individual n indicates the j th ordinal value for the
 18 walkability if the utility U_{lnq} lies within a particular range between $\mu_{q,j-1}$ and $\mu_{q,j}$. The cut-off
 19 parameters $\boldsymbol{\mu}_q = (\mu_{q,0}, \dots, \mu_{q,J})$ for each pedestrian-context class should be estimated. By
 20 assuming the probability density of the random disturbance ε_{lnq} as the normal distribution, the
 21 choice probability $P_{nl}(j|q)$ can be expressed as follows:

$$22 \quad P_{nl}(j|q) = \Phi(\mu_{q,j} - \boldsymbol{\beta}_q \mathbf{X}_{nl}) - \Phi(\mu_{q,j-1} - \boldsymbol{\beta}_q \mathbf{X}_{nl}) \quad (5)$$

23 where $\Phi(\cdot)$ represents the cumulative density function of the standard normal distribution.

24 To estimate the unknown parameters, the maximum likelihood method is employed in the
 25 present study. All the parameters associated with the class membership and the choice probability
 26 functions are estimated simultaneously. On the other hand, the optimal number of latent classes
 27 (Q) cannot be estimated simultaneously. Typically, the optimal number of classes is chosen based
 28 on a comparison of the model fit of a series of models with different number of classes. To measure
 29 and compare model fit, the present study employs Akaike information criterion (AIC) and
 30 Bayesian information criterion (BIC). In the both criteria, a lower value indicates a better
 31 goodness-of-fit.

32 ANALYSIS RESULTS

33 To identify the optimal number of latent classes, a series of models were estimated. Error!
 34 Reference source not found. presents the model fit of the one-, two-, three-, and four-latent class
 35 models. The value of both AIC and BIC continues to decrease as the number of class increase
 36 indicating that more latent classes result in a better fit. Considering the model fit and the

1 interpretability of classes, we have selected the four-class model as the optimal model for
 2 investigating the heterogeneous effects of pedestrian environments on walkability. Error!
 3 Reference source not found. provides the estimation results of the one-class model (Model 1) and
 4 the four-class model (Model 2).

5

6 **TABLE 2. Model Fit for the 1 to 4 Latent Class Membership Model.**

Number of classes	1	2	3	4
Number of parameters	15	40	65	90
Log-likelihood value	-84461.85	-84087.20	-83750.57	-83125.56
AIC	168953.69	168254.40	167631.15	166431.12
BIC	169093.45	168627.08	168236.75	167269.65

7

8

9 Model 1 presents the effects of the pedestrian environments on the walkability that are
 10 assumed to be homogeneous across different pedestrians. According to the estimation results,
 11 people tend to feel more walkable for a wider passage, and most of walking facilities tend to
 12 represent a positive response. In contrast to common safety considerations, the existence of central-
 13 line and mixed streets types exhibited a negative influence on the pedestrian satisfaction.
 14 Subsequently, pedestrians perceived a place more walkable when the area was characterised by a
 15 diversity of zoning types, yet too much crowding is experienced negatively as shown by the
 16 estimated coefficients. Furthermore, the residence indicator was also selected as a significant
 17 variable to influence the pedestrian walkability. In particular, the Seoul inhabitants, who hold an
 18 extensive spatial cognition of their routinely visited areas, “perceived distress”. The visiting
 19 frequency are used to unique define a routine visitor (i.e. every day and 3-5 days/week visitors).

20 Before moving on to the Latent Class Ordered Probit model (Model 2) estimation results,
 21 the methodological approach of this study is as follows: the Latent class framework was applied
 22 in this study. The Latent class framework indicated that relatively few classes are sufficiently
 23 flexible to capture quite complex patterns of heterogeneity (30). In this context, Latent class choice
 24 models are appropriate to distinguishing particular classes under the assumption that individuals’
 25 preferences in the same classes (i.e. membership groups) are homogeneous (25, 26).

26

27 From the estimation results of both Model 1 and 2, the distinctive correlation patterns of
 28 pedestrian environments on walkability were estimated. As stated before, the walking facilities,
 29 particularly the presence of fences, crossings, and trees as obstructions, were found having a
 30 positive influence. However, vehicle-oriented facilities were discovered to have negative effects
 31 on walkability.

32 Furthermore, the indicator of crowdedness of the street was estimated to have a negative
 33 influence. A mixed land-use index represents positive effects on walkability. The estimated results
 34 show that accessibility, which comprises the accessible distance for walking, generally positively
 35 contributes to pedestrian satisfaction levels (10) However, the crowdedness, the density of
 36 pedestrians, may lead to a negative influence on walkability (31). In this context, the pedestrian
 37 profiles may become the decisive factors to assess the pedestrian satisfaction level. Individual
 38 contextual attributes thus lead to distinctive responses in the choice of walkability as demonstrated
 39 by the Model 2 estimation results. In particular, it was discovered that dwellers (both in Seoul and
 40 Metropolitan area) tend to be more sensitive for responding the negative walkability than visitors.
 41 This may be explained by the spatial cognition and the density of residence in particular.

1 Model 2, latent class ordered probit model, first the four classes (the optimal number of
2 latent membership groups according to the model estimation results using NLogit 4 software) were
3 estimated. The profiles of latent classes were investigated, as it is the evidence shows that the
4 characteristics of respondents are not only influenced by the choice of walkability, but also by the
5 preferences of each class (being characterized by distinctive conditions and contexts). In other
6 words, this study contribute to the development of latent class choice approach in walkability
7 model, not only to distinguish the significant factors, but also explore the psychological indicators
8 and preserved contexts for testing the stated preference experiments. The latent class modelling is
9 deployed as an appropriate technique to detect the heterogeneous preferences in the contextual
10 variables, according to the theoretical review. In the next section, each latent classes is explored,
11 and distinct responses to their choices of (pedestrian) satisfaction are discovered in relation to
12 pedestrian context membership groups.

13 Class 1: Male ‘Walk-holic’ adults, who lived in the metropolitan area, outside of Seoul.

14 Class 2: ‘Female Seoul inhabitants’, who generally walking together with companion

15 Class 3: ‘Female Seoul commuters’, who usually walking together with companion

16 Class 4: Male ‘Saunters’, who dwelled in metropolitan area

17
18 This section describes the relationship between pedestrian environments and classes; that
19 is the heterogeneous responses (coefficients) of each pedestrian context group to pedestrian
20 environments from the estimation results (see Error! Reference source not found.).

21 Group 1 around a quarter (23.9%) of pedestrians belongs to this class. It is termed as ‘walk-
22 holic’ male adults. This group has a very strong base dependence on land-use variables, such as
23 the mixed land-use index and road types, especially in main-road survey spots. It can be interpreted
24 as the local facilities may cause to the significant indicator to determine the preference of
25 pedestrian walkability of Group 1.

26 Contradicting previous claim of Group 2 and group 3 are seems to be very similar classes,
27 which being predominantly populated with Seoul female dwellers. Yet their trip purpose is
28 distinctive, i.e. either walking commuters (i.e. utilitarian walking) or walkers for their discretionary
29 travel purpose. Group 2 seems to be unique latent class in pedestrians because their response to
30 pedestrian environments dramatically differs from overall tendency (i.e. the estimation results of
31 Model 2). The female Seoul dwellers seem to be much stressed from crowdedness during walking,
32 nor mixed land-use index which to be taken place the much volume of pedestrians in the walking
33 street. In this sense, each latent membership group has a distinctive spatial cognition level
34 depending on the locations. In particular, the locals who retained the knowledge of spatial
35 recognition stated a positive satisfaction level for their walking experiences. Furthermore, they
36 reacted also positively to accessible public transportation facilities, for which they have stronger
37 preferences than any other classes.

38 Moreover, Group 3 mainly comprises the ‘Seoul female commuters’, who prefer walking
39 together with someone for their commuting. As we discussed before, groups 2 and 3 have similar
40 profiles of each group members, however their response for pedestrian environments are not
41 identical. In other words, utilitarian pedestrian groups have a more negative influence than other
42 travel purposes. Group 3 shows this difference more clearly. The membership groups have a
43 negative effect from accessible public transportation facilities, yet they are positive at main roads
44 survey spots and crowded walking streets. This preference can be interpreted in relation to their
45 habitual and routine walking experiences which were accumulated during their previous
46 commuting walking trips. Both subway gates and bus stops in Seoul are crowded during the peak

1 hours, as well as the main-streets, which are consistently a high dense area for moving pedestrians
2 during the daytime.

3 Finally, Group 4, which is the largest class (28.7%), represents a large number of local
4 metropolitan males who prefer to walk alone. It has a marginally different response compared to
5 the overall tendency, especially for the width of walking street, mixed road types, and crossings.
6 However, it may lead to investigate the importance of trip purpose, which caused the distinctive
7 pedestrian walkability choice.

8
9 In summary, we identified the effects of pedestrian contexts on walkability in the
10 estimation results of Model 2, and compared it with Model 1. The most important indicators were
11 identified from the estimation results: trip purpose and spatial cognition, and gender. In addition,
12 the estimation results for Model 2 revealed the coefficients among the pedestrian environmental
13 factors on walkability, which influence the pedestrian walkability between discrete membership
14 groups by pedestrian contexts.

15 To be specific, ‘Female Seoul dwellers’, as membership group 2 in Model 2, yields the
16 most heterogeneous response on the pedestrian environments compared to other groups, which is
17 in contrast to the Model 1 estimation results. Additionally, the gender information is a substantial
18 indicator for the discrete latent classes: Males (Group 1 and 4) and Females (Group 2 and 3). Each
19 gender group shares some common characteristics regarding their pedestrian contexts; however,
20 they have distinctive choice preferences regarding the pedestrian environments, in relation to
21 walkability.

22 As indicated previously, the analysis results stem from the participants’ historical
23 experiences of walking and their spatial knowledge. As far as walkability is concerned, the
24 psychological conditions and acknowledged experiences of pedestrians in respect to their routine
25 walking behaviour may produce distinctive (individual) stated preferences for their walkability
26 choices. From the extensive findings of this analysis, it was discovered that the walking-trip
27 purposes and survey spots associated with the accumulated spatial cognition are substantial
28 indicators to establish the perceived preference of each membership group.

29

1 **TABLE 3. Model Estimation Results**

Model Component	Attributes		Model 1 (The one-class model)			Model 2 (The four-class model)											
						Class 1 (23.9%)			Class 2 (20.3%)			Class 3 (27.1%)			Class 4 (28.7%)		
			B	Std.	Z.	B	Std.	Z.	B	Std.	Z.	B	Std.	Z.	B	Std.	Z.
Pedestrian walkability choice part	Constants		0.5132	0.0215	23.92	1.0480	0.1901	5.51	-0.9515	0.2005	-4.75	0.8316	0.1495	5.56	1.4007	0.1638	8.55
	Walking road width		0.0214	0.0020	10.97	0.0500	0.0172	2.90	0.3694	0.0259	14.25	-0.0408	0.0121	-3.37	-0.0467	0.0128	-3.67
	Presence of central lines		-0.1168	0.0068	-17.24	-0.4493	0.0679	-6.62	0.6340	0.0863	7.35	-0.1487	0.0439	-3.38	-0.4222	0.0562	-7.51
	Number of total road lands		0.0557	0.0023	24.76	-0.0807	0.0256	-3.16	0.2708	0.0248	10.94	-0.1074	0.0201	-5.33	0.2396	0.0270	8.88
	Presence of walking obstacles		0.0375	0.0085	4.44	0.4340	0.0655	6.63	-0.6596	0.0887	-7.44	0.2167	0.0508	4.26	-0.0819	0.0517	-1.59
	Mixed traffic street		-0.0695	0.0067	-10.32	-0.7072	0.0797	-8.87	-0.0095	0.0671	-0.14	0.0421	0.0396	1.06	0.0944	0.0482	1.96
	Presence of sidewalk fence		0.0147	0.0054	2.73	0.0553	0.0507	1.09	-0.3339	0.0473	-7.05	0.1384	0.0301	4.59	0.0766	0.0339	2.26
	Presence of crossings		0.0249	0.0050	5.01	0.2826	0.0508	5.57	0.5210	0.0530	9.84	-0.0924	0.0321	-2.88	-0.2147	0.0412	-5.21
	Presence of stations in 50m	Bus and Subway	-0.0410	0.0104	-3.95	0.0161	0.0865	0.19	0.5539	0.1057	5.24	-0.3016	0.0481	-6.27	-0.2408	0.0632	-3.81
		Bus or Subway	0.0282	0.0071	4.00	-0.2511	0.0665	-3.78	-0.2464	0.0668	-3.69	0.2974	0.0414	7.19	0.1080	0.0453	2.38
		Nothing	0.0128	-	-	0.2350	-	-	-0.3075	-	-	0.0042	-	-	0.1328	-	-
	Crowdedness (Time-based)		-0.1149	0.0106	-10.86	-0.4778	0.0915	-5.22	-0.7274	0.1014	-7.18	0.3057	0.0656	4.66	-0.1569	0.0669	-2.35
	Land-use mix		0.3001	0.0164	18.30	1.1412	0.1521	7.50	-0.2289	0.1465	-1.56	0.3525	0.0984	3.58	0.0414	0.0995	0.42
	Type of spot	Main road	-0.0046	0.0083	-0.55	0.3715	0.0787	4.72	-1.4633	0.1106	-13.23	0.6160	0.0711	8.66	-0.0654	0.0656	-1.00
Residential area		-0.0395	0.0082	-4.84	-0.8551	0.0856	-9.99	2.3654	0.1577	15.00	-1.1001	0.1034	-10.63	0.1934	0.0886	2.18	
Others		0.0441	-	-	0.4836	-	-	-0.9022	-	-	0.4841	-	-	-0.1279	-	-	
Pedestrian – context class membership part	Constants		-	-	-	-0.3087	0.1466	-2.11	-0.3938	0.1213	-3.25	-0.1690	0.2202	-0.77	-	-	-
	Gender	Male	-	-	-	-0.0950	0.0265	-3.58	-0.1412	0.0276	-5.11	-0.1851	0.0398	-4.65	-	-	-
		Female	-	-	-	0.0950	-	-	0.1412	-	-	0.1851	-	-	-	-	-
	Age	Teenager	-	-	-	-0.6353	0.0742	-8.56	-0.5595	0.0733	-7.63	-0.7312	0.1110	-6.59	-	-	-
		Adults	-	-	-	0.1108	0.0412	2.69	0.0210	0.0422	0.50	0.2237	0.0696	3.22	-	-	-
		Elderly	-	-	-	0.5245	-	-	0.5385	-	-	0.5076	-	-	-	-	-
	Region	Dweller	-	-	-	-0.2525	0.0327	-7.72	0.1339	0.0283	4.74	0.1483	0.0436	3.40	-	-	-
		Stranger	-	-	-	0.2525	-	-	-0.1339	-	-	-0.1483	-	-	-	-	-
	Visiting frequency	Every day	-	-	-	0.1698	0.0462	3.67	0.3779	0.0480	7.88	0.3077	0.0662	4.65	-	-	-
		3-5 days/week	-	-	-	0.0701	0.0454	1.54	-0.1132	0.0453	-2.50	-0.3393	0.0692	-4.90	-	-	-
		1-2 days/week	-	-	-	-0.1162	0.0511	-2.27	-0.1804	0.0533	-3.38	-0.1368	0.0829	-1.65	-	-	-
	Rarely		-	-	-	-0.1238	-	-	-0.0843	-	-	0.1684	-	-	-	-	-
			-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Trip purpose	Utilitarian	-	-	-	0.0444	0.0270	1.65	0.0606	0.0279	2.17	0.1199	0.0427	2.81	-	-	-
Others		-	-	-	-0.0444	-	-	-0.0606	-	-	-0.1199	-	-	-	-	-	
Travel companion	Alone	-	-	-	-0.0644	0.0354	-1.82	-0.2203	0.0353	-6.23	-0.2698	0.0465	-5.81	-	-	-	
	With someone	-	-	-	0.0644	-	-	0.2203	-	-	0.2698	-	-	-	-	-	

Note: Estimates whose p-values are less than 0.05 are marked in bold.

2
3
4

1
2 **CONCLUSION**

3 With respect to the comparison between discrete choice model estimation results, a
4 substantial influence of pedestrian contexts on walkability was observed, which not only accounts
5 for the perceived preferences, but also produces the discrete membership groups in terms of latent
6 classes.

7 The estimation results of Latent Class Ordered Probit model, provided evidence for the
8 distinctive responses (i.e. diverse coefficients values) of walkability choices, in relation to
9 individuals' contextual characteristics. These findings using a Latent class ordered-probit model
10 indicated the significant influence of pedestrian contexts, which can lead to the perceived
11 pedestrian walkability. Furthermore, the analysis results of this study support that perceived
12 experiences and memories of individual groups may influence the walkability choices.

13 Moving on to the individual variability, i.e., pedestrian contextual attributes, such as spatial
14 cognition level and trip characteristics; these were shown to behave as the most significant
15 indicators, more than the pedestrian environments (especially facilities on the walking road),
16 which is the fruitful information for urban planners and decision makers.

17 Finally, this study also initialises and updates the knowledge of the relationship between
18 pedestrian environments and their perceived walkability with respect to personal contextual
19 variables. It thus provides valuable information to urban planners and decision makers to update
20 their best knowledge so they could design better walkable pedestrian environments, not only
21 concerning the residential inhabitants, but also respect the time-specific visitors, i.e. visiting
22 populations.

23
24 Although the contributions of this study, i.e. the influence of environmental factors on
25 walkability, and the significantly distinctive response in relation to the pedestrian (behavioural)
26 contexts, are considerable, this study is also limited to appraise how much the heterogeneous
27 individual contexts affects pedestrian walkability. This challenge may be addressed in futures
28 studies, which could employ advanced discrete choice modelling approaches.

29
30 In summary, future studies on the current topic, that is to investigate the external contextual
31 attributes associated with daily activity-travel patterns, are recommended. For instance, weather
32 conditions and the crowdedness by periods of day in a given area may generate distinctive choices
33 of walkability according to the individuals' routine activities.

34
35
36 **REFERNCES**

- 37 1. Gilderbloom, J. I., W. W. Riggs, and W. L. Meares. Does Walkability Matter? An
38 Examination of Walkability's Impact on Housing Values, Foreclosures and Crime. *Cities*, Vol. 42,
39 2015, pp. 13–24.
- 40
41 2. Lee, W. Do, W. Ectors, T. Bellemans, B. Kochan, D. Janssens, G. Wets, K. Choi, and C.-
42 H. Joh. Investigating Pedestrian Walkability Using a Multitude of Seoul Data Sources.
43 *Transportmetrica B: Transport Dynamics*, Vol. 6, No. 1, 2018, pp. 54–73.
- 44

- 1 3. Baran, P. K., D. a. Rodríguez, and A. J. Khattak. Space Syntax and Walking in a New
2 Urbanist and Suburban Neighbourhoods. *Journal of Urban Design*, Vol. 13, No. 1, 2008, pp. 5–
3 28.
- 4
- 5 4. Frank, L. D., T. L. Schmid, J. F. Sallis, J. Chapman, and B. E. Saelens. Linking Objectively
6 Measured Physical Activity with Objectively Measured Urban Form: Findings from
7 SMARTRAQ. *American Journal of Preventive Medicine*, Vol. 28, No. 2, 2005, pp. 117–125.
- 8
- 9 5. Frank, L. D., B. E. Saelens, K. E. Powell, and J. E. Chapman. Stepping towards Causation:
10 Do Built Environments or Neighborhood and Travel Preferences Explain Physical Activity,
11 Driving, and Obesity? *Social Science and Medicine*, Vol. 65, No. 9, 2007, pp. 1898–1914.
- 12
- 13 6. Manaugh, K., and A. El-Geneidy. Validating Walkability Indices: How Do Different
14 Households Respond to the Walkability of Their Neighborhood? *Transportation Research Part D:
15 Transport and Environment*, Vol. 16, No. 4, 2011, pp. 309–315.
- 16
- 17 7. Lefebvre-Ropars, G., C. Morency, P. A. Singleton, and K. J. Clifton. Spatial Transferability
18 Assessment of a Composite Walkability Index: The Pedestrian Index of the Environment (PIE).
19 *Transportation Research Part D: Transport and Environment*, Vol. 57, 2017, pp. 378–391.
- 20
- 21 8. Credit, K., and E. Mack. Place-Making and Performance: The Impact of Walkable Built
22 Environments on Business Performance in Phoenix and Boston. *Environment and Planning B:
23 Urban Analytics and City Science*, 2017, pp. 1–22.
- 24
- 25 9. Koschinsky, J., E. Talen, M. Alfonzo, and S. Lee. How Walkable Is Walker’s Paradise?
26 *Environment and Planning B: Urban Analytics and City Science*, Vol. 44, No. 2, 2017, pp. 343–
27 363.
- 28
- 29 10. Lamíquiz, P. J., and J. López-Domínguez. Effects of Built Environment on Walking at the
30 Neighbourhood Scale. A New Role for Street Networks by Modelling Their Configurational
31 Accessibility? *Transportation Research Part A: Policy and Practice*, Vol. 74, 2015, pp. 148–163.
- 32
- 33 11. Handy, S., X. Cao, and P. Mokhtarian. Correlation or Causality between the Built
34 Environment and Travel Behavior? Evidence from Northern California. *Transportation Research
35 Part D: Transport and Environment*, Vol. 10, No. 6, 2005, pp. 427–444.
- 36
- 37 12. Lindelöw, D., Å. Svensson, C. Sternudd, and M. Johansson. What Limits The Pedestrian?
38 Exploring Perceptions of Walking in the Built Environment and in the Context of Every-Day Life.
39 *Journal of Transport & Health*, Vol. 1, No. 4, 2014, p. pp 223-231.
- 40
- 41 13. Kim, S., S. Park, and J. S. Lee. Meso- or Micro-Scale? Environmental Factors Influencing
42 Pedestrian Satisfaction. *Transportation Research Part D: Transport and Environment*, Vol. 30,
43 2014, pp. 10–20.
- 44
- 45 14. Khalid, S., J. Wang, M. Shakeel, and X. Nan. Spatio-Temporal Analysis of the Street Crime
46 Hotspots in Faisalabad City of Pakistan. No. 2016-Janua, 2016.

- 1
2 15. Lindelöw, D., Å. Svensson, K. Brundell-Freij, and L. Winslott Hiselius. Satisfaction or
3 Compensation? The Interaction between Walking Preferences and Neighbourhood Design.
4 *Transportation Research Part D: Transport and Environment*, Vol. 50, 2017, pp. 520–532.
- 5
6 16. Tribby, C. P., H. J. Miller, B. B. Brown, C. M. Werner, and K. R. Smith. Assessing Built
7 Environment Walkability Using Activity-Space Summary Measures. *Journal of Transport and*
8 *Land Use*, Vol. 0, No. 0, 2015, pp. 187–207.
- 9
10 17. Erath, A., M. A. B. van Eggermond, S. A. Ordóñez, and K. W. Axhausen. Introducing the
11 Pedestrian Accessibility Tool: Walkability Analysis for a Geographic Information System.
12 *Transportation Research Record: Journal of the Transportation Research Board*, Vol. 2661, No. 1,
13 2017, pp. 51–61.
- 14
15 18. Jun, H.-J., and M. Hur. The Relationship between Walkability and Neighborhood Social
16 Environment: The Importance of Physical and Perceived Walkability. *Applied Geography*, Vol.
17 62, 2015, pp. 115–124.
- 18
19 19. Kang, B., A. V. Moudon, P. M. Hurvitz, and B. E. Saelens. Differences in Behavior, Time,
20 Location, and Built Environment between Objectively Measured Utilitarian and Recreational
21 Walking. *Transportation Research Part D: Transport and Environment*, Vol. 57, 2017, pp. 185–
22 194.
- 23
24 20. Seoul Metro Government. *Seoul Pedestrian Survey Report*. 2010.
- 25
26 21. Kang, C.-D. The Effects of Spatial Accessibility and Centrality to Land Use on Walking
27 in Seoul, Korea. *Cities*, Vol. 46, 2015, pp. 94–103.
- 28
29 22. Cervero, R., and K. Kockelman. Travel Demand and the 3Ds: Density, Diversity, and
30 Design. *Transportation Research Part D: Transport and Environment*, Vol. 2, No. 3, 1997, pp. 199–
31 219.
- 32
33 23. Gebel, K., A. E. Bauman, T. Sugiyama, and N. Owen. Mismatch between Perceived and
34 Objectively Assessed Neighborhood Walkability Attributes: Prospective Relationships with
35 Walking and Weight Gain. *Health and Place*, Vol. 17, No. 2, 2011, pp. 519–524.
- 36
37 24. Greene, W. H., and D. A. Hensher. A Latent Class Model for Discrete Choice Analysis:
38 Contrasts with Mixed Logit. *Transportation Research Part B: Methodological*, Vol. 37, No. 8,
39 2003, pp. 681–698.
- 40
41 25. Walker, J. L., and J. Li. Latent Lifestyle Preferences and Household Location Decisions.
42 *Journal of Geographical Systems*, Vol. 9, No. 1, 2007, pp. 77–101.
- 43
44 26. Feng, T., T. Arentze, and H. Timmermans. Capturing Preference Heterogeneity of Truck
45 Drivers' Route Choice Behavior with Context Effects Using a Latent Class Model. *European*
46 *Journal of Transport and Infrastructure Research*, Vol. 13, No. 4, 2013, pp. 259–273.

- 1
2 27. Molin, E., and K. Maat. Bicycle Parking Demand at Railway Stations: Capturing Price-
3 Walking Trade Offs. *Research in Transportation Economics*, Vol. 53, 2015, pp. 3–12.
4
5 28. Axsen, J., J. Bailey, and M. A. Castro. Preference and Lifestyle Heterogeneity among
6 Potential Plug-in Electric Vehicle Buyers. *Energy Economics*, Vol. 50, 2015, pp. 190–201.
7
8 29. Peer, S., J. Knockaert, and E. T. Verhoef. Train Commuters' Scheduling Preferences:
9 Evidence from a Large-Scale Peak Avoidance Experiment. *Transportation Research Part B:*
10 *Methodological*, Vol. 83, 2016, pp. 314–333.
11
12 30. McFadden, D., and K. Train. Mixed MNL Models for Discrete Response. *Journal of*
13 *Applied Econometrics*, Vol. 15, No. 5, 2000, pp. 447–470.
14
15 31. Feuillet, T., P. Salze, H. Charreire, M. Menai, C. Enaux, C. Perchoux, F. Hess, E. Kesse-
16 Guyot, S. Hercberg, C. Simon, C. Weber, and J.-M. Oppert. Built Environment in Local Relation
17 with Walking: Why Here and Not There? *Journal of Transport & Health*, 2016, pp. 1–13.
18
19
20